



JOHN-HENRY
ENTERPRISES, INC.

504.888.8989
Toll Free 800.992-7448

MAGNUM

Heavy Duty Butyl Degreaser

MAGNUM, concentrated heavy duty degreaser, is used to clean and degrease heavy equipment, automotive and marine engines, oil field equipment, tanks and shipping containers. MAGNUM is a potent aqueous blend of alkalies, biodegradable wetters and detergents, and chelates combined with a high level of a special water soluble solvent. Besides machinery and equipment, MAGNUM is great for cleaning and stripping composition, concrete, and tile floors, cleaning whitewall tires and wheels, preparing metal for painting, and general building maintenance. MAGNUM is fast acting, free rinsing, and phosphate free.

Tank Washing: latex, resins, lube oils & additives, 4-ADPA, tank exteriors.

Degreasing: Dilute up to 1 to 25 with water. For extreme oil removal, use undiluted for quickest response. For marine engine cleaning, and under-hood auto and truck cleaning, dilute with up to 3 parts water. For chassis cleaning, general fleet washing dilute Magnum with up to 25 parts water. **Tank Wash - Recirculation System:** use at 10% by weight. For extreme duty, such as set-up latex, resins, or dark lube oil additives, add 5% caustic soda to batch. **Tank Wash - Once Through System:** Introduce Magnum at 4-5 % by volume into system for normal washes. Difficult cleans will require presolve, as required by each product. **Food Grade Cleaning:** Use MAGNUM at 3-5% with >180°F water for Food Grade & Kosher Wash. Hot Water sanitize immediately after wash for 15 minutes maintaining 180°F.

SPECIFICATIONS FOR MAGNUM

Appearance.....	Clear, pale amber
pH.....	13±.5
Specific Gravity.....	1.0
Percent Active.....	30-35%
Flash Point.....	None
Dilution.....	Up to 25:1 with water
Foam.....	Low-Moderate
Hardwater Tolerance.....	Excellent
Ammonia.....	None
Butyl.....	Yes
Phosphate.....	None
Storage Stability.....	Excellent, indefinite
USDA Registered?.....	Yes

HMIS RATINGS			
Health	<input type="text" value="2"/>	Flammability	<input type="text" value="0"/>
Phys Haz	<input type="text" value="0"/>	Personal Protection	<input checked="" type="text" value="X"/>

PACKAGING
275 Gl Tote, JBC24841
55 gallon, JBC4135
6 gallon pail, JBC4138

